

Vapor-Stop

Vapor Stop

Vapor-Stop Primer is a pigmented two part epoxy designed to reduce moisture vapor emissions from concrete to acceptable levels for moisture and vapor sensitive floor systems and coatings. Vapor-Stop develops a tenacious bond to properly prepared surfaces and blocks the passage of moisture vapor. The system is applied easily by roller or squeegee without odors or flammability issues that could disrupt surrounding operations.

Features and Advantages:

- ☑ Withstands up to 15 lbs of Moisture Vapor Emissions
- ☑ Available in Cottonwood and Whisper Gray
- ☑ Self-Priming Material Allows for a Direct Bond
- ☑ Moderate to Fast Cure Profile
- ☑ Durable Physical Properties

Areas of Use:

- ✓ Service Bays
- ✓ Garage Floors
- ✓ Aircraft Hangers
- ✓ Locker Rooms
- ✓ Retail Flooring

Application Designs:

- ✓ Decorative Monolithic Flooring
- ✓ Decorative Flake Systems
- ✓ Beneath Non-Breathable and Moisture Sensitive Flooring
- ✓ Industrial Flooring Systems

Limitations:

- ✓ Will Not Bridge Cracking



1-800-535-3325

Tel: 562-989-2499

Fax: 562-989-3461

sales@deckcoatings.com

www.deckcoatings.com

2460 Lemon Ave.

Signal Hill, CA 90755 U.S.A.

©2002 by Versatile Building Products, Inc. Rev12/02