Material Safety Data Sheet

Section 1: Product Information

Manufacturer's Name / Address:Trade Name:5000 Polyurea B-Comp.Versatile Building ProductsChemical Family:Aliphatic Isocyanate

20420 S. Susana Road Mixture Carson, CA 90810

Info. Phone: Intended Use: Curing agent for 5000 310-632-6500 polyurea. A-comp.

Emergency Phone: Infotrac (800) 535-5053

Initial Issue Date: 7/1/5 Revision Date: 3/5/7 Prepared By: P. Dalvi

Section 2: Information on Ingredients

Ingredient (CAS #)	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Homopolymer of Hexamethylene	NE	NE	TWA	>50
Diisocyanate			.5mg/m^3,	
			STEL	
			1.0mg/m^3	
Hexamethylene Diisocyanate CAS 822-06-	NE	.005ppm TWA	ND	< 0.1
0				

VOC of Component: 0 g/L VOC As Applied: 0 g/L

Section 3: Physical Data

Boiling Point (°C):NDSpecific Gravity:1.1-1.15Vapor Pressure:NDMelting Point:NEVapor Density:>1Evaporation Rate:<1</th>(Air = 1)(Butyl Acetate = 1)

Solubility in Water: Partial pH: ND

Freezing Point ND Coefficient of Oil/Water Distribution:

Appearance and Odor: Clear to pale yellow liquid w/ fruity solvent odor.

Odor Threshold: ND

Section 4: Fire and Explosion Hazard

Flash Point (°C): 193 Conditions of Flammability: NA

Flammable Limits: LEL: ND UEL: ND

Autoignition Temperature (°C): ND

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, NOx

Sensitivity to Impact: None

Sensitivity to Static Discharge: May ignite product.

Extinguishing Media: Dry foam, chemical, carbon dioxide, water spray.

Special Firefighting Procedures:
Unusual Fire and Explosion
Use self-contained breathing apparatus and full protective clothing.
HDI vapors and other irritating toxic gases may be generated by

Hazards: combustion. Heated containers may rupture. Cool containers with water

spray.

Section 5: Health Hazard Data

Primary Routes of Entry: ⊠ Eye ⊠ Inhalation ⊠ Skin Contact □ Ingestion

Overexposure Effects: Dizziness, nausea, headaches, drowsiness, unconciousness and death.

Conditions Aggravated by Exposure: Respiratory tract conditions such as asthma and bronchitis: existing skin dermatitis and rashes may be aggravated by exposure . Pre-existing sensitization to isocyanates.

Health Hazards (Acute and Chronic Exposures):

Inhalation

Acute:

Irritation and soreness in the respiratory tract. Sore throat, coughing, discomfort, shortness of breath. Headache, dizziness, nausea, narcosis, fatigue and loss of appetite.

Chronic:

Isocyanate sensitization (chemical asthma.) Symptoms are similar to asthma and vary in intensity. Permanent lung damage may occur. Solvent content may lead to damage to the brain and nervous system.

Skin Contact

Acute:

Irritation, redness, and pain. Swelling, rash, scaling, and blistering. Skin sensitization may occur. Skin contact may lead to skin dermititis..

Chronic:

Chronic skin exposure will give effects similar to chronic inhalation. Those with skin sensitization may develop symptoms of exposure by small amounts of skin contact and/or inhalation.

Skin Absorption

Acute:

ND

Chronic:

ND

Eyes

Acute:

Vapors are irritating to the eye and can cause tearing, reddening, and swelling accompanied by a stinging sensation.

Chronic:

May result in corneal opacity (clouding of the eye surface). Prolonged vapor contact may cause conjunctivitis.

Ingestion

Acute:

Irritation of the gastrointestinal tract. Nausea. May be corrosive to the gastrointestinal lining. Vomiting may cause aspiration of the solvent resulting in chemical pneumonitis.

Chronic:

ND

Emergency and First Aid Procedures:

General:

Treat symptomatically. If not breathing administer artificial respiration.

Eves:

Immediatley rinse eyes with a direct stream of water for 15 minutes while holding the eyelids open. Seek medical attention if symptoms persist.

Skin:

Immediately wash contaminated skin with abundant water and mild soap. If symptoms persist seek medical advice.

Inhalation:

Remove effected person to fresh air. Administer artificial respiration if not breathing and unconcious. Give oxygen if breathing is labored. Seek medical attention. Symptoms may develop in a delayed manner relative to exposure.

Ingestion:

DO NOT INDUCE VOMITING. Give 1-2 cups of milk. Seek medical attention immediatley.

Carcinogenic Data:

NTP: ND OSHA: ND

IARC: Suspected 2B Carcinogen: Ethylbenzene (traceable impurity from xylene)

Toxicological Data:

Based on most toxic component: ORAL LD50(Rat) 10,000 g/KG, Dermal LD50 (Rabbit) 5000 g/KG, LC50 (Rat) 137-1150 ppm

Section 6: Reactivity Data
Chemical Stability: ⊠ Stable ☐ Unstable
Conditions to Avoid: Excessive heat and cold, moisture.
Incompatibility (Materials to Avoid): Strong oxidizers, concentrated acids, amines, water, and alcohols.
Hazardous Decomposition Products: From combustion: Carbon monoxide, carbon dioxide, NOx
Hazardous Polymerization (Reactivity) : ☐ Will Not Occur ☐ May Occur — Reacts w/ moisture and heat.
Section 7: Spill and Leak Procedures:

Steps to be Taken in Case of Material Release or Spillage: Evacuate non-essential personnel. Remove sources of ignition. Ventilate area. Contain spill. Notify proper authorities as necessary. Cover spill with absorbant material. Collect spill in appopriate waste container.

Waste Disposal Methods: Dispose of material in accordance with local, state and federal regulation.

Ecological Information: Low potential to effect aquatic organisms. Low potential to bioconcentrate.

Ecotoxicity: Based on most hazardous component: 96-h LC-50 (fathead minnow): 9090ug/L

Section 8: Special Protection Information

Engineering Controls: Ventilation to maintain TWA and STEL exposure limits. Shut off all open sources of ignition. Respiratory Protection: NIOSH approved respirator capable of filtering organic solvents must be worn when handling product.

Protective Gloves: Nitrile or butyl rubber gloves must be worn when handling the product. NO Vinyl gloves.

Eye Protection: Chemical goggles or face shield must be worn when handling the product.

Other protective Equipment: Eye wash station and emergency shower should be in close proximity to areas where product is being handled. Impermeable clothing should be worn. Clean contaminated clothing before reuse.

Section 9: Handling and Storage

General: Store away from open sources of ignition, excessive heat, excessive cold, oxidizers, strong acids, moisture, amines; store in well ventilated areas.

Section 10: Supplemental Information

Health: 2 Flammability: 1 Reactivity: 1

DOT Proper Shipping Name: Non-Regulated

Hazard Class: Non-Regulated UN Number: Non-Regulated Packing Group: NA

IMO Shipping Data: Non-Regulated ICAO/IATA Shipping Data: Non-Regulated

TSCA (Toxic Substance Control Act):

All components of this product are listed in the TSCA inventory.

CERCLA (Comprehensive Response Compensation and Liability Act):

Reportable quantity of HDI (CAS# 822-06-0): 100 lbs.

SARA Title III:

Section 311/312: Reactive Hazard.

Section 313 Reportable Ingredients: Hexamethylene Diisocyanate CAS 822-06-0

California Proposition 65: Below is a list of compounds known to the State of California to cause cancer, birth defects, or other reproductive harm:

None

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.