Material Safety Data Sheet

Section 1: Product Information								
Manufacturer's Name / Address:			Trade Name:	5310 A-Comp.				
Versatile Building Products			Chemical Family:	Polyester Polyol Solution				
20420 S. Susana Road	1							
Carson, CA 90810								
Info. Phone:			Intended Use:	Architectural Coating				
310-632-6500								
24 Hour Emergency	Phone:							
INFOTRAC (800) 53	5-5053							
Initial Issue Date:	8/29/6	Revision Date :	NA	Prepared By : P.Dalvi				

Section 2: Hazardous Ingredients						
Hazardous Component	OSHA PEL	ACGIH TLV	Other Limits	<u>% (Optional)</u>		
Propylene Glycol Monomethyl Ether	NE	NE	ND	0-1		
Acetate (CAS 108-65-6)						
Butyl Acetate(CAS 123-86-4)	100ppm TWA,150ppm	100ppm TWA,150ppm	ND	0-1		
	STEL	STEL				

VOC of Component: 137 g/L

VOC As Applied::92 g/L

Section 3: Physical Data					
ND	Specific Gravity:	1.10-1.15			
ND	Melting Point:	NE			
3.7	Evaporation Rate:	>1			
	(Butyl Acetate = 1)				
Partial	pH:	ND			
ND	-				
Coefficient of Oil/Water Distribution:					
Appearance and Odor:		Clear to cloudy clear w/ solvent odor.			
Odor Threshold:		ND			
	ND ND 3.7 Partial ND	NDSpecific Gravity:NDMelting Point:3.7Evaporation Rate: (Butyl Acetate = 1)Partial NDpH:Distribution:NDClear to cloudy clear w/			

Section 4: Fire and Explosion Hazard				
Flash Point (°C):	>37.7			
Conditions of Flammability:	NA			
Flammable Limits:	LEL: ND UEL: ND			
Autoignition Temperature (°C):	ND			
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide, NOx			
Sensitivity to Impact:	None			
Sensitivity to Static Discharge:	May ignite product.			
Extinguishing Media:	Dry foam, chemical, carbon dioxide.			
Special Firefighting Procedures:	Use self-contained breathing apparatus and impermeable clothing.			
Unusual Fire and Explosion	Heated containers may rupture. Cool containers with water spray.			
Hazards:				

Section 5: Health Hazard Data

Primary Routes of Entry: X Eye ⊠ Inhalation ⊠ Skin Contact Ingestion Overexposure Effects: Dizziness, nausea, headaches, drowsiness, unconciousness and death. Conditions Aggravated by Exposure: Respiratory tract conditions such as asthma and bronchitis: existing skin dermatitis and rashes may be aggravated by exposure. Health Hazards (Acute and Chronic Exposures): Eyes Acute: Irritation and redness. Chronic: ND Skin Contact Acute: Irritation, redness, and pain. Chronic: ND Skin Absorption Acute: ND Chronic: ND Inhalation Acute: Irritation of the respiratory tract. Labored breathing. Dizziness, headache, unconciousness, and death. Chronic: Kidney damage and severe pulmonary injury may occur. Ingestion Acute: Irritation of the gastrointestinal tract. Nausea. Chronic: ND **Emergency and First Aid Procedures:** General: Treat symptomatically. If not breathing administer artificial respiration. Eyes: Immediatley rinse eyes with a direct stream of water for 15 minutes while holding the eyelids open. Seek medical attention if symptoms persist. Skin: Immediately wash contaminated skin with abundant water and mild soap. I f symptoms persist seek medical advice. Inhalation: Remove effected person to fresh air. Administer artificial respiration if not breathing and unconcious. Give oxygen if breathing is labored. Seek medical attention.

Ingestion:

DO NOT INDUCE VOMITING. Seek medical attention immediatley. <u>Carcinogenic Data:</u> NTP: ND OSHA: ND IARC: Suspected 2B Carcinogen: Ethylbenzene (traceable impurity from xylene)

Toxicological Data:

Based on most toxic component: ORAL LD50(Rat) >42g/KG, Dermal LD50 (Rabbit) 25g/KG, LC50 (Rat) 21750ppm

Section 6: Reactivity Data

 Chemical Stability:
 □ Unstable

 Conditions to Avoid: Excessive heat and cold.

 Incompatibility (Materials to Avoid) : Strong oxidizers,concentrated acids.

 Hazardous Decomposition Products: From combustion: Carbon monoxide, carbon dioxide, NOX

 Hazardous Polymerization (Reactivity) : □ May Occur □ Will Not Occur

Section 7: Spill and Leak Procedures:

Steps to be Taken in Case of Material Release or Spillage: Evacuate non-essential personnel. Remove sources of ignition. Ventilate area. Contain spill. Notify proper authorities as necessary. Cover spill with absorbant material. Collect spill in appopriate waste container.

Waste Disposal Methods: Dispose of material in accordance with local, state and federal regulation.

Ecological Information: Low potential to effect aquatic organisms. Low potential to bioconcentrate.

Ecotoxicity: Based on most hazardous component: 96-h LC-50 (fathead minnow) : 161mg/L 48 - h LC50(dphnid): 408mg/L

Section 8: Special Protection Information

Engineering Controls: Ventilation to maintain TWA and STEL exposure limits. Shut off all open sources of ignition. **Respiratory Protection**: NIOSH approved repirator capable of filtering organic solvents must be worn when handling product.

Protective Gloves: Neoprene ro butyl rubber gloves must be worn when handling the product. NO Vinyl gloves. **Eye Protection**: Chemical goggles or face shield must be worn when handling the product.

Other protective Equipment: Eye wash station and emergency shower should be in close proximity to areas where product is being handled. Impermeable clothing should be worn. Clean contaminated clothing before reuse.

Section 9: Handling and Storage

General: Store away from open sources of ignition, excessive heat, excessive cold, oxidizers, strong acids; store in well ventilated areas.

Section 10: Supplemental Information

Health: 1 Flammability: 2 Reactivity: 0

DOT Proper Shipping Name: Resin Solution - Flammable Hazard Class : 3 UN Number: UN1866 Packing Group: III IMO Shipping Data: Resin Solution//3.3//UN1866//PGIII - Flammable Labels ICAO/IATA Shipping Data : Resin Solution//3//UN1866//PGIII - Flammable Labels

TSCA (Toxic Substance Control Act) :

All components of this product are listed in the TSCA inventory. **CERCLA (Comprehensive Response Compensation and Liability Act)**: Reportable quantity Xylene (CAS# 1330-20) 100lbs **SARA Title III**: Section 311/312 Immediate health hazard, Delayed health, Fire. Section 313 Reportable Ingredients: Xylene (CAS 1330-20-7), Ethyl Benzene (CAS 100-41-4)

California Proposition 65: Below is a list of compounds known to the State of California to cause cancer, birth defects, or other reproductive harm: None

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.