



Topped off with polyureas

igh-performance clear polyurea coatings supplied by Versatile Building Products, Carson, CA, pro-

vided the protective finishing touch on the decorative flooring applications shown here.

Clockwise from left:

An adhesive-backed template was used to create this pattern, with coloring provided by concrete stain. The topcoat is Polyurea 5000, a zero-VOC, low-odor coating with an extended pot life of 30 minutes or more.

The concrete countertops in this backyard barbecue setting owe their mirror-like, high-gloss appearance to Polyurea 5073, a low-VOC coating that offers an extended pot life (45 minutes), shorter cure time, and ultra-thin film.

Polyurea 5073 also was used to topcoat the decorative floor in this retail store.

The floor design was created using Kwik Top an acrylic cementitious microtoping, and Versa-Stain, a water-based acrylic concrete stain.

Polyurea 5000 was applied as a topcoat to this decorative garage floor created with a liquid epoxy flake flooring system, RollonRock, also supplied by Versatile Building Products. The appearance of depth and richness is obtained by roller application of the epoxy material, broadcast distribution of acrylic flake, and finishing with the clear polyurea.

These clear polyurea finishes are reported to offer high levels of resistance to UV exposure, chemicals, and abrasion.

(All but lower right photo of car):
Photos courtesy of ColourWorks, Placerville, CA.

(Car shot):

Photo courtesy of The Garage People of New Jersey, Newark, NJ.





